



NACE ISO 15156-03 SERVICE DATA SHEET

H₂S Partial Pressure (Check the most applicable)

- Equal To or Less Than 0.5 psia (3.4 kpa)
- Greater Than 0.5 psia (3.4 kpa) and Less Than or Equal To 1.5 psia (10 kpa)
- Greater Than 1.5 psia (10 kpa) and Less Than or Equal To 3.0 psia (20 kpa)
- Greater Than 3.0 psia (20 kpa) and Less Than or Equal To 15 psia (100 kpa)
- Greater Than 15 psia (100 kpa) and Less Than or Equal To 30 psia (200 kpa)
- Greater Than 30 psia (200 kpa) and Less Than or Equal To 50 psia (350 kpa)
- Greater Than 50 psia (350 kpa) and Less Than or Equal To 150 psia (1000 kpa)
- Greater Than 150 psia (1000 kpa) and Less Than or Equal To 200 psia (1400 kpa)
- Greater Than 200 psia (1400 kpa) and Less Than or Equal To 300 psia (2100 kpa)
- Greater Than 300 psia (2100 kpa) and Less Than or Equal To 600 psia (4100 kpa)
- Greater Than 600 psia (4100 kpa)

pH (Check the most applicable)

- Less Than 3.5
- Equal to or Greater Than 3.5 and Less Than 4.5
- Equal to or Greater Than 4.5

Chlorides (Check the most applicable)

- Equal to or Less Than 50 mg/L
- Greater than 50 mg/L

Free Sulfur (Check the most applicable)

- Yes
- No

Operating Temperature (Check the most applicable)

- Equal To or Less than 140 °F (60 °C)
- Greater Than 140 °F (60 °C) and Less Than or Equal To 150 °F (65 °C)
- Greater Than 150 °F (65 °C) and Less Than or Equal To 275 °F (135 °C)
- Greater Than 275 °F (135 °C) and Less Than or Equal To 300 °F (149 °C)
- Greater Than 300 °F (149 °C) and Less Than or Equal To 350 °F (177 °C)
- Greater Than 350 °F (177 °C) and Less Than or Equal To 400 °F (204 °C)
- Greater Than 400 °F (204 °C) and Less Than or Equal To 425 °F (220 °C)
- Greater Than 425 °F (220 °C) and Less Than or Equal To 450 °F (232 °C)
- Greater Than 450 °F (232 °C)